



受け枠:Bタイプは
厚さ5mmのゴムパッキン付き

荷重	桁穴 mm	型式記号	グレーチング本体				受枠				
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠 形式	B寸法 mm	A寸法 mm	H mm	重量 kg
T25	300	AGBL30-50	395	400	50	12.6	A	420	420	61	9.3
							B	420	420	66	9.7
	350	AGBL35-50	450	450	50	15.9	A	470	470	61	10.4
							B	470	470	66	10.8
	400	AGBL40-55	501	500	55	20.5	A	520	520	66	12.0
							B	520	520	71	12.5
	450	AGBL45-60	550	550	60	27.2	A	570	570	71	13.6
							B	570	570	76	14.2
	500	AGBL50-65	607	607	65	33.5	A	630	630	76	15.6
							B	630	630	81	16.2
	600	AGBL60-75	713	713	75	51.8	A	735	735	86	19.6
							B	735	735	91	20.3
T20	300	AGBL30-44	395	400	44	9.9	A	420	420	56	8.9
							B	420	420	61	9.3
	350	AGBL35-50	450	450	50	15.9	A	470	470	61	10.4
							B	470	470	66	10.8
	400	AGBL40-50	501	500	50	18.9	A	520	520	61	11.5
							B	520	520	66	12.0
	450	AGBL45-55	550	550	55	24.9	A	570	570	66	13.1
							B	570	570	71	13.6
	500	AGBL50-55	607	607	55	29.1	A	630	630	66	14.4
							B	630	630	71	15.0
	600	AGBL60-65	713	713	65	45.2	A	735	735	76	18.2
							B	735	735	81	18.9

荷重	桁穴 mm	型式記号	グレーチング本体				受枠				
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠 形式	B寸法 mm	A寸法 mm	H mm	重量 kg
T14 ~T6	300	AGBL30-38	395	400	38	8.8	A	420	420	50	8.4
							B	420	420	56	8.9
	350	AGBL35-44	455	455	44	12.4	A	470	470	56	10.0
							B	470	470	61	10.5
	400	AGBL40-44	515	515	44	15.6	A	520	520	56	11.3
							B	520	520	61	11.8
	450	AGBL45-50	550	550	50	23.0	A	570	570	61	12.6
							B	570	570	66	13.1
	500	AGBL50-50	607	607	50	26.9	A	630	630	61	13.9
							B	630	630	66	14.4
	600	AGBL60-55	713	713	55	39.2	A	735	735	66	16.8
							B	735	735	71	17.5
T2	300	AGBL30-32	395	400	32	7.6	A	420	420	44	8.0
							B	420	420	50	8.4
	350	AGBL35-32	455	455	32	9.6	A	470	470	44	9.0
							B	470	470	50	9.5
	400	AGBL40-32	515	515	32	12.0	A	520	520	44	10.1
							B	520	520	50	10.7
	450	AGBL45-32	545	550	32	13.3	A	570	570	44	10.7
							B	570	570	50	11.4
	500	AGBL50-38	605	605	38	18.4	A	630	630	50	12.5
							B	630	630	56	13.2
	600	AGBL60-38	695	700	38	23.8	A	735	735	50	14.3
							B	735	735	56	15.1

材質	SS 400	
処理	本体	溶融亜鉛メッキ
	枠	樹脂系塗装