



荷重	溝幅	型式記号	グレーチング本体				受 枠		
			b寸法	a寸法	h	重量・kg	寸法	重量・kg	
T 20	200	AGL20-44	995	300	44	20.2	A	L56X60X6	11.6
							B	L61X60X6	11.9
	250	AGL25-50		350	50	28.2	A	L61X60X6	11.9
							B	L66X60X6	12.4
	300	AGL30-55		400	55	33.9	A	L66X60X6	12.4
							B	L71X60X6	12.6
	350	AGL35-60		450	60	40.5	A	L71X60X6	12.6
							B	L76X60X6	13.0
400	AGL40-65	500	65	46.6	A	L76X60X6	13.0		
					B	L81X60X6	13.8		
450	AGL45-75	550	75	57.6	A	L86X60X6	14.0		
					B	L91X60X6	14.4		
500	AGL50-75	600	75	62.3	A	L86X60X6	14.0		
					B	L91X60X6	14.4		
T 14	200	AGL20-38	995	300	38	18.1	A	L50X60X6	10.9
							B	L56X60X6	11.6
	250	AGL25-44		350	44	22.5	A	L56X60X6	11.6
							B	L61X60X6	11.9
	300	AGL30-50		400	50	31.4	A	L61X60X6	11.9
							B	L66X60X6	12.4
	350	AGL35-50		450	50	34.5	A	L61X60X6	11.9
							B	L66X60X6	12.4
	400	AGL40-55		500	55	41.4	A	L66X60X6	12.4
							B	L71X60X6	12.6
450	AGL45-55	550	55	45.0	A	L66X60X6	12.4		
					B	L71X60X6	12.6		
500	AGL50-65	600	65	54.6	A	L76X60X6	13.0		
					B	L81X60X6	13.8		

受け枠のBタイプは
厚さ5mmのゴムパッキン付き

ベアリングバーピッチ30.0mm (h38~ h44)

ベアリングバーピッチ35.3mm (h50以上)

図名	ボルト固定式グレーチング			符号	AGL	縮尺
設計	鈴 2009.02.03	照 査	野 2009.02.03	承 認	記事	
	木		島	梅 2009.02.03		
伊藤鉄工株式会社					図番	G09A00065
						葉内