


受け枠のBタイプは厚さ5mmのゴムパッキン付き



材質	SS 400
処本	溶融亜鉛メッキ
理枠	樹脂系塗装

h50以上は蓋が2枚割となります。

荷重	溝幅 mm	型式記号	グレーチング本体				受枠		
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠 形式	寸法 mm	重量 kg
T25	200	AGLCN20-38	995	300	38	29.0	A	L50×60×6	10.9
							B	L56×60×6	11.6
	250	AGLCN25-44		350	44	38.0	A	L56×60×6	11.6
							B	L61×60×6	11.9
	300	AGLCN30-44		400	44	42.0	A	L56×60×6	11.6
							B	L61×60×6	11.9
	350	AGLCN35-50		450	50	67.0	A	L61×60×6	11.9
							B	L66×60×6	12.4
	400	AGLCN40-50		500	50	74.5	A	L61×60×6	11.9
							B	L66×60×6	12.4
	450	AGLCN45-50		550	50	81.5	A	L61×60×6	11.9
							B	L66×60×6	12.4
	500	AGLCN50-50		600	50	88.5	A	L61×60×6	11.9
							B	L66×60×6	12.4

荷重	溝幅 mm	型式記号	グレーチング本体				受枠		
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠 形式	寸法 mm	重量 kg
T20	200	AGLCN20-32	995	300	32	25.5	A	L44×60×6	9.6
							B	L50×60×6	10.9
	250	AGLCN25-38		350	38	33.0	A	L50×60×6	10.9
							B	L56×60×6	11.6
	300	AGLCN30-44		400	44	42.0	A	L56×60×6	11.6
							B	L61×60×6	11.9
	350	AGLCN35-44		450	44	46.8	A	L56×60×6	11.6
							B	L61×60×6	11.9
	400	AGLCN40-50		500	50	74.5	A	L61×60×6	11.9
							B	L66×60×6	12.4
	450	AGLCN45-50		550	50	81.5	A	L61×60×6	11.9
							B	L66×60×6	12.4
	500	AGLCN50-50		600	50	88.5	A	L61×60×6	11.9
							B	L66×60×6	12.4

荷重	溝幅 mm	型式記号	グレーチング本体				受枠		
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠 形式	寸法 mm	重量 kg
T14	200	AGLCN20-32	995	300	32	25.5	A	L44×60×6	9.6
							B	L50×60×6	10.9
	250	AGLCN25-32		350	32	28.8	A	L44×60×6	9.6
							B	L50×60×6	11.9
	300	AGLCN30-38		400	38	38.0	A	L50×60×6	10.9
							B	L56×60×6	11.6
	350	AGLCN35-38		450	38	41.4	A	L50×60×6	10.9
							B	L56×60×6	11.6
	400	AGLCN40-44		500	44	51.5	A	L56×60×6	11.6
							B	L61×60×6	11.9
	450	AGLCN45-44		550	44	55.9	A	L56×60×6	11.6
							B	L61×60×6	11.9
	500	AGLCN50-44		600	44	60.6	A	L56×60×6	11.6
							B	L61×60×6	11.9