


受け枠:Bタイプは厚さ5mmのゴムパッキン付き

荷重	樹穴 mm	型式記号	グレーチング本体				受枠				
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠形式	B寸法 mm	A寸法 mm	H mm	重量 kg
T25	300	AGBNL30-50	395	400	50	12.6	A	420	420	61	9.3
							B	420	420	66	9.7
	350	AGBNL35-50	450	450	50	15.9	A	470	470	61	10.4
							B	470	470	66	10.8
	400	AGBNL40-55	501	500	55	20.5	A	520	520	66	12.0
							B	520	520	71	12.5
450	AGBNL45-60	550	550	60	27.2	A	570	570	71	13.6	
						B	570	570	76	14.2	
500	AGBNL50-65	600	600	65	33.5	A	630	630	76	15.6	
						B	630	630	81	16.2	
600	AGBNL60-75	700	700	75	51.8	A	735	735	86	19.6	
						B	735	735	91	20.3	
T20	300	AGBNL30-44	395	400	44	9.9	A	420	420	56	8.9
							B	420	420	61	9.3
	350	AGBNL35-50	450	450	50	15.9	A	470	470	61	10.4
							B	470	470	66	10.8
	400	AGBNL40-50	501	500	50	18.9	A	520	520	61	11.5
							B	520	520	66	12.0
450	AGBNL45-55	550	550	55	24.9	A	570	570	66	13.1	
						B	570	570	71	13.6	
500	AGBNL50-55	600	600	55	29.1	A	630	630	66	14.4	
						B	630	630	71	15.0	
600	AGBNL60-65	700	700	65	45.2	A	735	735	76	18.2	
						B	735	735	81	18.9	

荷重	樹穴	型式記号	グレーチング本体				受枠				
			b寸法 mm	a寸法 mm	h mm	重量 kg	受枠形式	B寸法 mm	A寸法 mm	H mm	重量 kg
T14~T6	300	AGBNL30-38	395	400	38	8.8	A	420	420	50	8.4
							B	420	420	56	8.9
	350	AGBNL35-44	450	450	44	12.4	A	470	470	56	10.0
							B	470	470	61	10.5
	400	AGBNL40-44	500	500	44	15.6	A	520	520	56	11.3
							B	520	520	61	11.8
450	AGBNL45-50	550	550	50	23.0	A	570	570	61	12.6	
						B	570	570	66	13.1	
500	AGBNL50-50	600	600	50	26.9	A	630	630	61	13.9	
						B	630	630	66	14.4	
600	AGBNL60-55	700	700	55	39.2	A	735	735	66	16.8	
						B	735	735	71	17.5	
T2	300	AGBNL30-32	395	400	32	7.6	A	420	420	44	8.0
							B	420	420	50	8.4
	350	AGBNL35-32	450	450	32	9.6	A	470	470	44	9.0
							B	470	470	50	9.5
	400	AGBNL40-32	500	500	32	12.0	A	520	520	44	10.1
							B	520	520	50	10.7
450	AGBNL45-32	545	550	32	13.3	A	570	570	44	10.7	
						B	570	570	50	11.4	
500	AGBNL50-38	600	600	38	18.4	A	630	630	50	12.5	
						B	630	630	56	13.2	
600	AGBNL60-38	695	700	38	23.8	A	735	735	50	14.3	
						B	735	735	56	15.1	



スベリ止め 詳細図

材質	SS 400	
処理	本体	溶融亜鉛メッキ
	枠	樹脂系塗装