



AGN側溝用 AGHN歩道用 受枠AGF

荷重	溝幅	型式記号	グレーチング本体			受枠		
			b寸法	a寸法	h	重量kg	寸法	重量kg
T 2 0	150	AGN15-32	995	250	32	9.3	L38×60×6	9.2
	200	AGN20-44		300	44	16.5	L50×60×6	10.3
	250	AGN25-44		350	44	18.8	L50×60×6	10.3
	300	AGN30-50		400	50	27.8	L56×60×6	11.1
	350	AGN35-55		450	55	33.5	L61×60×6	11.4
	400	AGN40-55		500	55	37.1	L61×60×6	11.4
	450	AGN45-65		550	65	46.8	L71×60×6	12.1
T 1 4	500	AGN50-75	995	600	75	58.9	L81×60×6	13.3
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-32		300	32	12.2	L31×60×6	9.2
	250	AGN25-38		350	38	16.4	L44×60×6	9.7
	300	AGN30-44		400	44	21.3	L50×60×6	10.3
	350	AGN35-50		450	50	30.7	L56×60×6	11.1
	400	AGN40-50		500	50	34.1	L56×60×6	11.1
T 6	450	AGN45-55	995	550	55	40.3	L61×60×6	11.4
	500	AGN50-60		600	60	48.3	L66×60×6	11.8
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-32		300	25	9.7	L31×60×6	8.0
	250	AGN25-38		350	32	13.8	L38×60×6	9.2
	300	AGN30-38		400	38	18.6	L44×60×6	9.7
	350	AGN35-44		450	44	23.5	L50×60×6	10.3
T 2	400	AGN40-44	995	500	44	26.0	L50×60×6	10.3
	450	AGN45-50		550	50	37.0	L56×60×6	11.1
	500	AGN50-50		600	50	40.4	L56×60×6	11.1
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-25		300	25	9.7	L31×60×6	8.0
	250	AGN25-25		350	25	12.5	L31×60×6	8.0
	300	AGN30-25		400	25	14.3	L31×60×6	8.0
T 2	350	AGN35-25	995	450	25	15.9	L31×60×6	8.0
	400	AGN40-32		500	32	19.3	L38×60×6	9.2
	450	AGN45-32		550	32	21.0	L38×60×6	9.2
	500	AGN50-32		600	32	22.9	L38×60×6	9.2
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-25		300	25	9.7	L31×60×6	8.0
	250	AGN25-25		350	25	12.5	L31×60×6	8.0

AGN横断溝用 受枠AGF

荷重	溝幅	型式記号	グレーチング本体			受枠		
			b寸法	a寸法	h	重量kg	寸法	重量kg
T 2 0	150	AGN15-32	995	250	32	9.3	L38×60×6	9.2
	200	AGN20-38		300	38	14.4	L44×60×6	9.7
	250	AGN25-44		350	44	18.8	L50×60×6	10.3
	300	AGN30-50		400	50	27.8	L56×60×6	11.1
	350	AGN35-55		450	55	33.5	L61×60×6	11.4
	400	AGN40-60		500	60	40.8	L66×60×6	11.8
	450	AGN45-65		550	65	46.8	L71×60×6	12.1
T 1 4	500	AGN50-65	995	600	65	51.1	L71×60×6	12.1
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-32		300	32	12.2	L38×60×6	9.2
	250	AGN25-38		350	38	16.4	L44×60×6	9.7
	300	AGN30-44		400	44	21.3	L50×60×6	10.3
	350	AGN35-50		450	50	30.7	L56×60×6	11.1
	400	AGN40-50		500	50	34.1	L56×60×6	11.1
T 6	450	AGN45-55	995	550	55	40.3	L61×60×6	11.4
	500	AGN50-55		600	55	44.0	L61×60×6	11.4
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-32		300	32	12.2	L38×60×6	9.2
	250	AGN25-38		350	38	16.4	L44×60×6	9.7
	300	AGN30-44		400	44	21.3	L50×60×6	10.3
	350	AGN35-44		450	44	23.5	L50×60×6	10.3
T 2	400	AGN40-50	995	500	50	34.1	L56×60×6	11.1
	450	AGN45-50		550	50	37.0	L56×60×6	11.1
	500	AGN50-55		600	55	44.0	L61×60×6	11.4
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-25		300	25	9.7	L31×60×6	8.0
	250	AGN25-25		350	25	12.5	L31×60×6	8.0
	300	AGN30-32		400	32	15.8	L38×60×6	9.2
T 2	350	AGN35-32	995	450	32	17.4	L38×60×6	9.2
	400	AGN40-38		500	38	22.7	L44×60×6	9.7
	450	AGN40-38		550	38	24.7	L44×60×6	9.7
	500	AGN50-44		600	44	30.8	L50×60×6	10.3
	150	AGN15-25		250	25	7.5	L31×60×6	8.0
	200	AGN20-25		300	25	9.7	L31×60×6	8.0
	250	AGN25-25		350	25	12.5	L31×60×6	8.0

ベアリングバーピッチ 30.0mm (h19~ h44)
 ベアリングバーピッチ 35.3mm (h50以上)

部品表

部番	部品名	材質	備考	数量
①	グレーチング	S S 4 0 0	溶融亜鉛メッキ	1
②	受枠	S S 4 0 0	錆止め塗装	1

図名	側溝用・横断溝用 ノンスリップ鋼製グレーチング			符号	AGN	縮尺	A / A
設	鈴 2009.02.03 木	照 野 2009.02.03 島	承 梅 2009.02.03 村	記事	記事		
伊藤鉄工株式会社				図番	G 0 9 A 0 2 0 0 7	葉 内	