



スベリ止め詳細図

材質	SS 400	
処理	本体	溶融亜鉛メッキ
	枠	樹脂系塗装

荷重	柵穴 mm	型式記号	グレーチング本体				受枠			
			b寸法 mm	a寸法 mm	h mm	重量 kg	B寸法 mm	A寸法 mm	H mm	重量 kg
T25	300	AGBCN30-38	400	400	38	13.6	420	420	44	7.6
	350	AGBCN35-38	450	450	38	17.3	475	475	44	8.7
	400	AGBCN40-44	500	500	44	26.9	535	535	50	10.3
	450	AGBCN45-44	550	550	44	30.1	570	570	50	10.9
	500	AGBCN50-50	304+290	600	50	55.0	630	630	56	13.5
	600	AGBCN60-50	349+349	700	50	73.0	735	735	56	15.5
T20	300	AGBCN30-32	400	400	32	11.6	420	420	38	7.1
	350	AGBCN35-38	450	450	38	17.3	475	475	44	8.7
	400	AGBCN40-38	500	500	38	23.7	535	535	44	9.7
	450	AGBCN45-44	550	550	44	30.1	570	570	50	10.9
	500	AGBCN50-44	600	600	44	36.5	625	625	50	12.5
	600	AGBCN60-50	349+349	700	50	73.0	735	735	56	15.5

荷重	柵穴 mm	型式記号	グレーチング本体				受枠			
			b寸法 mm	a寸法 mm	h mm	重量 kg	B寸法 mm	A寸法 mm	H mm	重量 kg
T14 ~T6	300	AGBCN30-25	400	400	25	9.1	420	420	31	6.6
	350	AGBCN35-32	450	450	32	14.8	475	475	38	8.6
	400	AGBCN40-32	500	500	32	20.5	535	535	38	9.0
	450	AGBCN45-38	550	550	38	26.5	570	570	44	10.8
	500	AGBCN50-38	600	600	38	32.1	625	625	44	11.4
	600	AGBCN60-44	700	700	44	46.6	720	720	50	14.4
	T2	300	AGBCN30-19	400	400	19	6.4	417	417	23.5
350		AGBCN35-25	450	450	25	11.7	475	475	31	7.5
400		AGBCN40-25	500	500	25	15.1	535	535	31	8.5
450		AGBCN45-25	550	550	25	17.1	570	570	31	9.0
500		AGBCN50-25	600	600	25	20.9	625	625	31	9.9
600		AGBCN60-32	700	700	32	34.7	720	720	38	12.8